LARGEDISPLAY Protected against electromagnetic interference The display is connected to the Reflex on one of the two robust communication protocol RS485 THE VEHICLE CAN BE EQUIPPED WITH TWO LARGE DISPLAYS ON EACH SIDE Large outdoor display to monitor production in real time

- > 3 digits of 51/2" LED GREEN
- ➤ The protective lens is replaceable
- > Visible at 200 feet
- ▶ Readable in full sun
- > Display in Lbs, Kg or Ton
- ►Clear and non-diffused led
- ➤ Intensity automatically adjustable to ambient brightness
- >For application on ground and underground
- ➤ Water protection: resists powerful high-pressure water jets
- ➤ Designed to accept fast atmospheric variations
- ➤ Built to withstand aggressive environment
 - ➤ Enclosure entirely in stainless steel
 - ► Electronics and LED fully sealed
 - ➤ Resist to impacts and jet of high pressure

SPECIFICATIONS:

- _ Supply: 9-30 Volt
- Led: High brithness tehnology
- Dimension WxHxD: 33x22x4 cm
- Enclosure: Stainless Steel
- _ Weight: ?? gr
- Operating temperature range: -50 à 80°C
- _ Sealed monitor: IP69K
- Communication: RS485
- Wiring jacket: TPE shielded
- _ Cable lenght; 10 meters
- Connector M12
- Protection againts EMI
- _ Conforme EMC Directive 2004/108/EC
- Shock and vibration resistant
- Option: wireless communication



